

Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
LC-7513	box	2	-	MPEG4 / H.264 / MJPEG	dual	supported	1-way	-
LC-7523/ LC-7533	fixed dome	2	-	MPEG4 / H.264 / MJPEG	dual	supported	1-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
ACM-5711 / ACM-5811	box	-	-	MPEG4	single	supported	2-way	-
TCM-5001	box	-	-	H.264 / MPEG4	single	supported	2-way	-
TCM-5311	box	A1D-310-V4.07.10-AC	1280 x 720	H.264 / MPEG4	single	supported	2-way	-
TCM-5601 /	box	-	1280 x 1024	H.264 / MPEG4	single	supported	2-way	-
ACM-1231 / ACM-1232	bullet	-	1280 x 1024	MPEG4	single	supported	2-way	-
ACM-1511	bullet	A1D-220-V3.11.13-AC	1280 x 1024	MPEG4	single	supported	2-way	-
ACM-4000 / ACM-4001	cube	-	-	MPEG4	single	supported	2-way	-
ACM-4201	cube	A1D-220-V3.09.14-AC	1280 x 1024	MPEG4	single	supported	2-way	-
ACM-4200	cube	A1D-220-V3.09.14-AC	-	MPEG4	single	supported	2-way	-
ACM-3401	fixed dome	A1D-220-V3.09.14-AC	1280 x 1024	MPEG4	single	supported	2-way	-
ACM-5320HP (PAL)	box	A1D-M2N-V2.09.11-AC	-	MPEG4	single	supported	-	-
SED-2610	video server	-	D1 / CIF	MPEG4	single	supported	2-way	-
SED-2120B 1-CH	video server	A1D-M2N-V2.06.12-NB	-	MPEG4	single	supported	-	-
CAM-5140 / CAM-5130/CAM-5150	box	A1D-POV-V1.13.03-AC	-	MPEG4	single	-	-	-
TCM-5312	box	-	1280 x 1024	H.264 / MPEG4	single	supported	2-way	-
TCM-4301	cube	-	1280 x 1024	H.264 / MPEG4	single	supported	2-way	-
TCM-3401 / TCM-3411	fixed dome	A1D-310-V4.08.05-AC	1280 x 1024	H.264 / MPEG4	single	supported	2-way	-
ACM-3511 / ACM-7411	fixed dome	-	1280 x 1024	MPEG4	single	supported	2-way	-
ACM-3701 / ACM-3703	fixed dome	-	1280 x 1024	MPEG4	single	supported	-	-
TCM-3001 / TCM-3011 / TCM-7011	fixed dome	-	-	H.264 / MPEG4	single	supported	2-way	-
TCM-4101/TCM-4001	cube	-	-	H.264 / MPEG4	single	supported	2-way	-
ACM-1011	bullet	-	-	MPEG4	single	supported	2-way	-
CAM-5301 / CAM-5321	box	-	-	MPEG4	single	supported	1-way	-
ACM-3601 / ACM-3603	fixed dome	-	-	MPEG4	single	supported	-	-
ACM-3001 / ACM-3311 / ACM-3011	fixed dome	-	-	MPEG4	single	supported	2-way	-
ACM5611	box	-	1280 x 1024	MPEG4	single	supported	2-way	-
ACM-8511	IP PTZ	-	-	MPEG4	single	supported	2-way	-
CAM-6510	speed dome	-	-	MPEG4	single	-	-	-
ACD-2100	video server	-	-	MPEG4	single	supported	2-way	-
ACD-2200	video server	A4D-R2N-V2.07.05-AC	-	MPEG4	single	supported	2-way	-
ACD-2300	video server	-	-	MPEG4	single	supported	2-way	-
ACD-2400	video server	-	-	MPEG4	single	supported	2-way	-
SED-2610	video server	-	-	MPEG4	single	supported	2-way	-
TCD-2100 / TCD-2500	video server	-	-	MPEG4	single	supported	2-way	-
ACM-3411	fixed dome	A1D-220-V3.09.14-AC	1280 x 1024	MPEG4	single	supported	2-way	-
ACM-8201/ACM-8211	IP PTZ	-	1280 x 1024	MPEG4	single	supported	2-way	-
ACM-1431/ACM-1432	bullet	-	-	MPEG4	single	supported	2-way	-
ACM-7511	fixed dome	-	-	MPEG4	single	supported	2-way	-
ACM 5601	box	-	1280 x 1024	MPEG4	single	supported	2-way	-
TCM- 1511	bullet	-	1280 x 1024	H.264 / MPEG4	single	supported	2-way	-
TCM-3511/TCM-7411	fixed dome	-	1280 x 1024	H.264 / MPEG4	single	supported	2-way	-
TCM- 4201	cube	-	1280 x 1024	H.264 / MPEG4	single	supported	2-way	-
TCM- 6630	speed dome	-	1280 x 1024	H.264 / MPEG4	single	supported	2-way	-
TCM-7811	fixed dome	-	1280 x 720	H.264 / MPEG4	single	supported	2-way	-
TCM-1232/TCM-1011	bullet	-	1280 x 1024	H.264 / MPEG4	single	supported	2-way	-
KCM-5111/KCM-5211/KCM-5211E/ KCM-5311/ KCM-5311E	box	-	1280 x 720	H.264 / MPEG4	single	supported	2-way	-
KCM-3211/ KCM-7111/ KCM-7211	fixed dome	-	1280 x 720	H.264 / MPEG4	single	supported	2-way	-
CAM-6610/6310	speed dome	-	-	MPEG4	single	supported	2-way	-

Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
1300	box	64327	1280 x 1024	MJPEG	dual	supported	-	-
1310	box	-	1280 x 1024	MJPEG	dual	supported	-	-
1305DN	box	65140	1280 x 1024	H.264	dual	supported	-	-
2115	box/compact	-	1920 x 1080	H.264	dual	supported	-	-
2100	box	64327	1600 x 1200	MJPEG	dual	supported	-	-
2210	box	-	1600 x 1200	MJPEG	dual	supported	-	-
2105	box	65139	1280 x 1024	H.264	dual	supported	-	-
2805	box	-	1920 x 1080	H.264	dual	supported	-	-
2815 / 2815DN	box	-	1920 x 1080	H.264	dual	supported	-	-
2825 / 2825IR / 2825DN	bullet	-	1920 x 1080	H.264	dual	supported	-	-
3100	box	64327	2048 x 1536	MJPEG	dual	supported	-	-
3110	box	-	2048 x 1536	MJPEG	dual	supported	-	-
2110	box	-	1600 x 1200	MJPEG	dual	supported	-	-
1355	dome	-	1280 x 1024	H.264	dual	supported	-	-
1325/1325DN/1325IR	bullet	-	-	H.264	dual	-	-	-
2155	dome	-	-	H.264	dual	supported	-	-
1115	box	-	1280 x 1024	H.264	dual	-	-	-
1125	bullet	-	1280 x 1024	H.264	dual	-	-	-
2125	bullet/IR Illuminator	-	1920 x 1080	H.264	dual	supported	-	-
3130	box	64329	2048 x 1536	MJPEG	dual	supported	-	-
3105DN	box	65140	2048 x 1536	H.264	dual	supported	-	-
3115	box/compact	-	2048 x 1536	H.264	dual	supported	-	-
3125	bullet/IR Illuminator	-	2048 x 1536	H.264	dual	supported	-	-
3135	box	-	2048 x 1536	H.264	dual	supported	-	-
3155	dome	-	2048 x 1536	H.264	dual	supported	-	-
5125	bullet/IR Illuminator	-	2592 x 1944	H.264	dual	supported	-	-
5100	box	64327	2592 x 1944	MJPEG	dual	supported	-	-
5110	box	-	2592 x 1944	MJPEG	dual	supported	-	-
5105	box	65139	2592 x 1944	H.264	dual	supported	-	-
5155	dome/PTZ	-	2592 x 1944	H.264	dual	supported	-	-
8180	panoramic	-	1600 x 1200	MJPEG	single	-	-	-
8185	panoramic	-	1600 x 1200	H.264	single	-	-	-
8185DN	panoramic	-	1600 x 1200	H.264	single	-	-	-
8360	panoramic	65006	1600 x 1200	MJPEG	single	-	-	-
8365	panoramic	65131	1600 x 1200	H.264	single	-	-	-
8365DN	panoramic	-	1600 x 1200	H.264	single	-	-	-
10005	box	-	3648 x 2752	H.264	single	supported	-	-
5115	box	-	2592 x 1944	H.264	dual	supported	-	-
10115	box	-	-	H.264	dual	supported	-	-

Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
211	box	-	640x480	MPEG4	-	supported	-	-
211M	box	-	1280x1024	MPEG4	-	supported	2-way	-
211W	box	-	640x480	MPEG4	-	supported	2-way	-
M1011/M1011-W	box	-	640x480	MPEG4	-	supported	-	-
M1031-W	cube	-	640 x 480	H.264 / MPEG4	-	supported	-	-
M1054	cube	-	640 x 480	H.264 / MPEG4	-	supported	2-way	-
M1103	box	-	800 x 600	H.264	-	supported	-	-
M1104	box	-	1280 x 1024	H.264	-	supported	-	-
M1113	box	-	800 x 600	H.264	-	supported	-	-
M1114	box	-	1280 x 800	H.264	-	supported	-	-
P1131	box	-	640 x 480	H.264 / MPEG4	-	supported	2-way	-
P1343 / 1343-E	box	-	800 x 600	H.264	-	supported	2-way	-
P1344 / P1344-E	box	-	1280 x 800	H.264	-	supported	2-way	-
P1346 / 1346-E	box	-	2048 x 1536	H.264	-	supported	2-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
P1347 / P1347-E	box	-	2560 x 1920	H.264	-	supported	2-way	-
Q1755 / Q1755-E	box	-	1920 x 1080	H.264	-	supported	2-way	-
209FD / 209FD-R	dome	-	640 x 480	MPEG4	-	supported	-	-
209MFD / 209MFD-R	dome	-	1280 x 1024	MPEG4	-	supported	-	-
216FD / 216FD-V	dome	-	640 x 480	MPEG4	-	supported	2-way	-
216MFD / 216MFD-V	dome	-	1280 x 1024	MPEG4	-	supported	2-way	-
225FD	dome	-	640 x 480	MPEG4	-	supported	-	-
M3011	dome	-	640 x 480	H.264 / MPEG4	-	supported	-	-
M3014	dome	-	1280 x 800	H.264	-	supported	-	-
M3113-R	dome	-	800 x 600	H.264	-	supported	-	-
M3114-R	dome	-	1280 x 800	H.264	-	supported	-	-
M3203 / M3203-V	dome	-	800 x 600	H.264	-	supported	-	-
M3204 / M3204-V	dome	-	1280 x 800	H.264	-	supported	-	-
P3301 / P3301-V	dome	5.11	640 x 480	H.264	-	supported	2-way	-
P3304 / P3304-V	dome	-	1280 x 800	H.264	-	supported	2-way	-
P3343 / P3343-V / P3343-VE	dome	-	800 x 600	H.264	-	supported	2-way	-
P3344 / P3346 / P3344-V / P3346-V / P3344-VE	dome	5.20.2	1280 x 800	H.264	-	supported	2-way	-
P3346-VE	dome	5.20.2	1280 x 800	H.264	-	supported	2-way	-
212 PTZ / 212 PTZ-V	PTZ	-	640 x 480	MPEG4	-	supported	2-way	-
214 PTZ	PTZ	-	704 x 480	MPEG4	-	supported	2-way	-
215 PTZ / 215 PTZ-Z	PTZ	4.49	704 x 480	MPEG4	single	supported	2-way	-
232D+	PTZ	-	704 x 480	MPEG4	-	supported	-	-
233D	PTZ	-	704 x 480	MPEG4	-	supported	2-way	-
P5532	PTZ	-	720 x 480	H.264	-	supported	2-way	-
P5332-E	PTZ	-	720 x 480	H.264	-	supported	-	-
P5534	PTZ	-	1280 x 720	H.264	-	supported	2-way	-
P5534-E	PTZ	-	1280 x 720	H.264	-	supported	-	-
Q6032-E	PTZ	-	704 x 480	H.264	-	supported	-	-
Q6034	PTZ	-	1280 x 720	H.264	-	supported	2-way	-
Q6034-E	PTZ	-	1280 x 720	H.264	-	supported	-	-
Q1910 / Q1910-E	Thermal	-	720 x 576	H.264	-	supported	2-way	-
Q1921 / Q1921-E	Thermal	-	768 x 576	H.264	-	supported	2-way	-
241S	video server	-	704 x 576	MPEG4	-	supported	-	-
243SA	video server	-	704 x 576	MPEG4	-	supported	2-way	-
247S	video server	-	704 x 576	MPEG4	-	supported	1-way	-
M7001	video server	-	720 x 480	H.264	-	supported	1-way	-
O7401	video server	-	720 x 576	H.264	-	supported	2-way	-
241O	video server	-	720 x 480	MPEG4	-	supported	-	-
241OA	video server	-	768 x 480	MPEG4	-	supported	2-way	-
O7404	video server	-	720 x 480	H.264	-	supported	2-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
BIP-1600c / (BIP2-1600c-dn)	box	BIP-1600c-1.5-0	-	H.264	single	supported	-	-
BIP2-1280c / (BIP2-1280-dn)	box	-	1280 x 480	H.264	-	supported	-	-
BIP2-640c / (BIP2-640c-dn)	box	-	640 x 480	H.264	-	supported	-	-
BIP2-1000c / (BIP2-1000c-dn)	box	-	1027 x 768	H.264	-	supported	-	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
FD-100Ap	fixed dome	V2.3.7.8	1280 x 800	MJPEG / MPEG4 / H.264	single	-	1-way	-
OSD-040D	PTZ	V3.0.7.5	720 x 480	MJPEG / MPEG4 / H.264	single	-	1-way	-
VS-01Ap	video server	V3.0.6.7	720 x 480	MJPEG / MPEG4 / H.264	single	-	1-way	-
MD-100AP	mini dome	V3.0.6.28	1280 x 800	MJPEG / MPEG4	single	-	1-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
DNC-240SEW	PTZ	4.09-39	720 x 576	H.264 / MJPEG	single	supported	-	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
NH-073	box	D20110729NSA	1920x1080P	H.264	dual	supported	1-way	-
VI-A54300	fixed dome	D20110325ANS	1920x1080P	H.264	dual	supported	1-way	-
NV-062	box	D20110711ANS	1920x1080P	H.264	dual	supported	1-way	-
NH-820-18NI	PTZ	Z12011014nsa SLID-ba37	1920x1080P	H.264	dual	supported	1-way	-
NV-063	box	D20110711ANS	1920x1080P	H.264	dual	supported	1-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
DS-2CD852MF(2MP)	box	V2.0 100329	1280 x 960	H.264	single	supported	1-way	-
DS-2CD862MF-E/N	box	V2.0 100329	VGA	H.264	single	supported	1-way	-
DS-2CD752M(-E) / DS-2CD752MF-FB(H) / DS-2CD752MF-IFB(H)	dome	-	1600 x 1200	H.264	single	supported	-	-
DS-2CD762MF-FB(H) / DS-2CD762MF-IFB(H)	dome	-	1280 x 960	H.264	single	supported	-	-
DS-2CD833F-E(W)	box	-	640 x 480	H.264	single	supported	1-way	-
DS-2CD893PF(NF)-E(W) / DS-2CD893PFWD(NFWD)-E	box	-	704 x 480	H.264	single	supported	1-way	-
DS-2CD863PF(NF)-E(W)	box	-	1280 x 960	H.264	single	supported	1-way	-
DS-2CD854F-E(W)	box	-	2048 x 1536	H.264	single	supported	1-way	-
DS-2CD883F-E(W)	box	-	2560 x 1920	H.264	single	supported	1-way	-
DS-2CD733F-E(I)	dome	-	640 x 480	H.264	single	supported	1-way	-
DS-2CD793PF(NF)-E(I) / DS-2CD793PFWD(NFWD)-E(I)	dome	-	740x 480	H.264	single	supported	1-way	-
DS-2CD763PF(NF)-E(I)	dome	-	1280 x 960	H.264	single	supported	1-way	-
DS-2CD753F-E(I)	dome	-	1600 x 1200	H.264	single	supported	1-way	-
DS-2CD754F-E / DS-2CD754F-E	dome	-	2048 x 1536	H.264	single	supported	1-way	-
DS-2CD754F-E / DS-2CD754F-E	dome	-	2048 x 1536	H.264	single	supported	1-way	-
DS-2CD754FWD-E / DS-2CD754FWD-EI	dome	-	1920 x 1080	H.264	single	supported	1-way	-
DS-2CD754FWD-EI	dome	-	1920 x 1080	H.264	single	supported	1-way	-
DS-2CD783F-E	dome	-	2560 x 1920	H.264	single	supported	1-way	-
DS-2CD7133-E	dome	-	640 x 480	H.264	single	supported	1-way	-
DS-2CD7153F-E(I)	dome	-	1600 x 1200	H.264	single	supported	1-way	-
DS-2CD8133F-E(W)(I)	cube	-	640 x 480	H.264	single	supported	1-way	-
DS-2CD8153F-E(W)(I)	cube	-	1600 x 1200	H.264	single	supported	1-way	-
DS-2CD8253F-E(I)	bullet	-	1600 x 1200	H.264	single	supported	1-way	-
DS-2CD8254F-EI	bullet	-	2048 x 1536	H.264	single	supported	1-way	-
DS-2CD886BF-E	box	V2.0 100629	2560 x 1920	H.264	single	supported	1-way	-
Hik (DS-2DF1-617)	PTZ	V2.0 090523	740 x 480	H.264	single	supported	1-way	-
DS-2CD853F-E(W) (2MP)	box	-	1600 x 1200	H.264	single	supported	1-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
HS-CI5020	box	00.00.008-Beta	D1 / CIF	H.264	supported	supported	1-way	-
HS-CI532H	dome	00.00.007-Beta	D1 / CIF	H.264	dual	supported	-	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
HEB-2MPN1	box	2.1.6	1600 x 1200	H.264 / MJPEG	single	supported	1-way	-
HTC-2MPB1	box	2.1.7	1600 x 1200	H.264 / MJPEG	single	supported	1-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
HLC-81M	box	-	1280 x 1024	MPEG4 / MJPEG	single	supported	2-way	-
HLC-81L	box	-	1280 x 1024	MPEG4 / MJPEG	single	-	2-way	-
HLV-1CI	cube	-	-	MPEG4 / MJPEG	-	-	2-way	-
HLC-84M	cube	-	-	MPEG4 / MJPEG	-	-	2-way	-
HLC-84V	cube	-	-	MPEG4 / MJPEG	-	-	2-way	-
HLC-83M	cube	-	-	MPEG4 / MJPEG	-	-	2-way	-
HLC83V	cube	-	-	MPEG4	-	-	2-way	-
HLC-81L	box	-	-	MPEG4 / MJPEG	single	-	2-way	-
HLC-81AG	box	V1.10	720 x 480	MPEG4 / MJPEG	single	-	2-way	-
HLC-81AD	box	-	-	H.264 / JPEG / MPEG4	-	-	2-way	-
HLV-1CI	fixed dome	-	-	MPEG4 / MJPEG	single	-	-	-
HLV-WAD	vandal dome	-	-	H.264 / JPEG / MPEG4	-	-	2-way	-
HLV-1WAG	vandal dome	-	-	H.264 / JPEG / MPEG4	-	-	2-way	-
HLV-CAD/P	fixed dome	V1.06	-	H.264 / JPEG / MPEG4	single	supported	2-way	-
HLV-1CM	fixed dome	-	-	JPEG / MPEG4	-	-	2-way	-
HLC-1CM	fixed dome	-	-	JPEG / MPEG4	-	-	2-way	-
HLV-1CI	fixed dome	-	-	H.264 / JPEG / MPEG4	-	-	2-way	-
HLV-1NAD	fixed dome	-	-	H.264 / JPEG / MPEG4	single	-	2-way	-
HLC-1NAG	fixed dome	V1.01.10	-	H.264 / JPEG / MPEG4	-	supported	2-way	-
HLC-15M	fixed dome	-	-	MPEG4 / MJPEG	-	-	2-way	-
HLC-15V	fixed dome	-	-	MPEG4 / MJPEG	-	-	-	-
HLC-15I	fixed dome	-	-	MPEG4 / MJPEG	-	-	-	-
HLC-79AD	outdoor IR bullet	V1.01.14	1600 x 1200	H.264 / JPEG / MPEG4	single	supported	2-way	-
HLC-79AG	outdoor IR bullet	-	-	H.264 / JPEG / MPEG4	-	-	2-way	-
HLC79AG	outdoor IR bullet	-	-	H.264 / JPEG / MPEG4	-	-	-	-
HLC79M	outdoor IR bullet	-	-	MPEG4 / MJPEG	-	-	-	-
HLC-79G	outdoor IR bullet	-	-	MPEG4 / MJPEG	-	-	-	-
HLC-7RI	outdoor IR bullet	-	-	MPEG4 / MJPEG	-	-	-	-
HLT-87ZA	PTZ	-	-	H.264 / JPEG / MPEG4	-	-	-	-
HLT-87Z	PTZ	-	-	MPEG4 / MJPEG	-	-	-	-
HLT-86F	PTZ	-	-	MPEG4 / MJPEG	-	-	-	-
HLV-1CAD	fixed dome	-	-	H.264 / JPEG / MPEG4	single	supported	2-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
NCD-2000P	fix dome	51110.21644.100	1920 x 1080	H.264	dual	supported	1-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
IOEYE 510	box	V2.8/9(100219)	704x480	MJPEG	single	supported	-	-
IOEYE 732N	bullet	V3.2/3(101130)	1920x1080	H.264 / MJPEG	single	supported	2-way	-
IOEYE 755	bullet	V3.0/8(100702)	2560x1920	MJPEG	single	supported	-	-
IOEYE A25S	fixed dome	V3.0/8(100702)	2560 x 1920	H.264 / MJPEG	single	supported	-	-

Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
GNC-761	box	-	640 x 480	MPEG4 / MJPEG	dual	supported	2-way	-
GNC-762	box	-	640 x 480	MPEG4 / MJPEG	dual	supported	2-way	-
GNC-861MEVA	box	-			dual	supported	2-way	-
GNC-862ME	box	-				supported	2-way	-
GNC-771						supported	2-way	-
GNC-772	bullet	-	640 x 480	MPEG4	dual	supported	2-way	-
GNC-783	bullet	-	640 x 480	MPEG4	dual	supported	2-way	-
GNC-871MEVA	bullet	-	1280 x 800	H.264 / MPEG4 / MJPEG	dual	supported	2-way	-
GNC-851MEVA	dome	-	1280 x 800	H.264 / MPEG4 / MJPEG	dual	supported	2-way	-
GNC-852ME	dome	-	1600 x 1200	H.264 / MPEG4 / MJPEG	dual	supported	2-way	-
GNC-720	cube	-	640 x 480	MPEG4	dual	supported	2-way	-

Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
NIC 835	box	FW Version: X.2.1.8 HW Version: BN-X.006-T Mac Address: 00:0B:67:00:8E:27	640 x 480	MPEG4	single	supported	1-way	-
NCB 855	box	Kernel Version: Linux version 2.6.10_mvl401_IPNC-1.0.8.18MS / BIOS Version: x U-Boot 1.2.0 (Nov 26 2008 - 09:51:06) IPNC- U-1.0.2.01M / App Version: C076_00-02-07_MS / ActivX Version: 1,0,0,40		MJPEG4	single	supported	1-way	-
NDF820	fixed dome	Linux version 2.6.18_v1.5.1 _2M_SH00 / AP_01-00- 06_2M_SH00		MPEG4	single	supported	-	-
NIC 830-HN5	fixed dome	FW Version: X.2.1.17 HW Version: BN-X.006-T Mac Address: 00:0B:67:00:C5:63	640 x 480	MJPEG4	single	-	-	-
NC 836	box	FW Version: X.2.1.7 HW Version: BN-X.006-T Mac Address:	640 x 480	MJPEG4	single	supported	1-way	-
NCB 855PRO-HP5	box	Kernel Version: Linux version 2.6.18_v1.5.1 _2M_MS03 App Version: AP_01-00-59- 07_2M_MS03	1920 x 1080	H264 MPGE4/ MJPEG	single	supported	1-way	-
NDZ 860	PTZ	FW Version: X.3.0.6.1 HW Version: BN Mac Address: 00:0B:67:00:D5:A6	640 x 480	MJPEG4	single	supported	-	-
NCB 855	box	Kernel Version: Linux version 2.6.10_mvl401_IPNC-1.0.8.18MS BIOS Version:x U-Boot 1.2.0 (Nov 26 2008 - 09:51:06) IPNC- U-1.0.2.01M App Version: C076_00-02- 07_MS ActivX Version: 1,0,0,40	1280 x 720	MJPEG4	single	supported	1-way	-

Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
NCR 875	bullet	Kernel Version: Linux version 2.6.10_mv401_IPNC-1.0.8.20MS BIOS Version: U-Boot 1.2.0 (Nov 11 2009 - 11:17:25) IPNC-U-1.0.2.03M App Version: C076_00-02-20_MS ActiveX Version: 1,0,0,40	1280 x 720	MJPEG4	single	supported	1-way	-
NDR 890	fixed dome	Kernel Version: Linux version 2.6.10_mv401_IPNC-1.0.8.20MS BIOS Version: U-Boot 1.2.0 (Nov 11 2009 - 11:17:25) IPNC-U-1.0.2.03M App Version: C076_00-02-20_MS ActiveX Version: 1,0,0,40	1280 x 720	MJPEG4	single	-	-	-
NDF 820	fixed dome	Linux version 2.6.18_v1.5.1_2M_MS02 AP_01-00-57_2M_MS02	1920 x 1080	H264 MPGE4/ MJPEG	single	supported	-	-
NCR 870	bullet	*内核版本: Linux version 2.6.18_v1.5.1_2M_SH00 应用程序版本: AP_01-00-06_2M_SH00*	1920 x 1080	H264 MPGE4/ MJPEG	single	supported	-	-
NDF821/NDF 831/NDF 891	fixed dome	Kernel Version: Linux version 2.6.18_v1.5.1_2M_MS02 App Version: AP_01-00-57_2M_MS02	1920 x 1080	H264 MPGE4/ MJPEG	single	supported	-	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
O24	dome	4.0.4.18	2408 x 1536	JPEG	single	-	-	-
M22	box	3.4.5.10	2408 x 1960	JPEG	single	-	-	-

Panasonic

Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
WV-NW502S	fixed dome	-	2408 x 1536	MPEG4 / MJPEG	single	supported	-	-
WV-SP306 / WV-SP305 / WV-SP302	Bullet	-	1280 x 960	MPEG4 / MJPEG	single	supported	-	-
WV-SP336 / WV-SP335 / WV-SP332	Bullet	-	1280 x 960	MPEG4 / MJPEG	single	supported	-	-
WV-SP105 / 102	Bullet	-	1280 x 960	MPEG4 / MJPEG	single	supported	-	-
WV-SC385	PTZ	-	1280 x 960	H.264 / MPEG4 / MJPEG	single	supported	-	-
WV-NP502/WV-MW502	Bullet	1.02/1.04/1.04	-	H.264 / MPEG4 / MJPEG	single/dual	supported	-	-
WV-NF302/WV-NP304	fixed dome	-	1280 x 960	MPEG4 / MJPEG	single	supported	-	-
WV-NS954(9500 series) / WV-NS964(9600 series)	PTZ	-	640 x 480	MPEG4 / MJPEG	single	supported	-	-
WV-NS202A	PTZ	-	640 x 480	MPEG4 / MJPEG	single	supported	-	-
WV-NW484S	fixed dome	-	640 x 480	MPEG4 / MJPEG	single	supported	-	-
WV-NF284	fixed dome	-	640 x 480	MPEG4 / MJPEG	single	supported	-	-
WV-NP244	Box	1.70E+02	640 x 480	MPEG4 / MJPEG	single	supported	-	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
P600	box	2.0.3_225	1600 x 1200	H.264 / MJPEG	dual	supported	2-way	-
PV6901	video server	2.0.0.1	720 x 480	H.264 / MJPEG	dual	supported	2-way	-
P463T	PTZ	2.30R95.05.PX	720 x 480	MPEG / MJPEG	single	-	1-way	-
PD636E	fish eye	2.0.0411	1600 x 1200	H.264	single	supported	2-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
IXE20N	box	.4.9081-A1.3484 / 9081-A1.1-090	1920 x 1080	H.264	dual	supported	1-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
SND 3080 / 3080F	fixed dome	1.10_100312	720 x 480	MPEG4 / H.264	single	supported	-	-
SNV 3080	fixed dome	1.10_100312	720 x 480	MPEG4 / H.264	single	supported	1-way	-
SBD 5080 / 5080F	fixed dome	1.10_100720	1280 x 1024	MPEG4 / H.264 / MJPEG	single	-	1-way	-
SBV 5080 / SNB 5000	fixed dome	1.20_100927	1280 x 1024	MPEG4 / H.264 / MJPEG	single	supported	1-way	-
SNB 3000	box	SNB-3000N-v1.12_100812	720 x 480	H.264	single	-	1-way	-
SNB 3370 / 3370TH / 3301	PTZ	1.0.6/4.3.0.0/0.82.0.0	720 x 480	H.264	single	-	1-way	-
SND 1010	fixed dome	1.03_101210	640 x 480	MPEG4 / H.264 / MJPEG	single	-	1-way	-
SNB 1000	box	-	640 x 480	MPEG4 / H.264 / MJPEG	single	-	-	-
SNV 3120	fixed dome	1.00_100927	720 x 480	MPEG4 / H.264 / MJPEG	single	-	1-way	-
SNP 3120 / 3120V / 3120H	dome	-	720 x 480	MPEG4 / H.264 / MJPEG	single	-	1-way	-
SNP 3430H	PTZ	1.02_101122	720 x 480	MPEG4 / H.264 / MJPEG	single	-	1-way	-
SNV 5010	flat camera	1.00_100927	1280 x 1024	MPEG4 / H.264 / MJPEG	single	-	-	-
SNB 5000	box	-	1280 x 1024	MPEG4 / H.264 / MJPEG	single	-	1-way	-
SNC 1300	dome	-	1280 x 1024	MPEG4 / MJPEG	single	-	-	-
SND 3080C / 3080F	box	-	740 x 480	MPEG4 / H.264 / MJPEG	single	-	-	-
SNB 2000	box	-	640 x 480	MPEG4 / H.264 / MJPEG	single	-	-	-
SNB 1000	dome	-	640 x 480	MPEG4 / H.264 / MJPEG	single	-	-	-
SND 460V	dome	-	740 x 480	MPEG4 / MJPEG	single	-	-	-
SND 560	dome	-	740 x 480	MPEG4 / MJPEG	single	-	-	-
SNP 1000A	PTZ	-	740 x 480	MPEG4 / MJPEG	single	-	-	-
SNC C7478 / C7478C	smart dome	-	740 x 480	MPEG4 / MJPEG	single	-	1-way	-
SNC C7225 / C6225	smart dome	-	740 x 480	MPEG4 / MJPEG	single	-	1-way	-
SBC C5399	fixed dome	-	740 x 480	MPEG4 / H.264 / MJPEG	single	-	1-way	-
SNC 5368	box	-	740 x 480	MPEG4 / H.264 / MJPEG	single	-	1-way	-
SNC B2335	box	-	740 x 480	MPEG4 / H.264 / MJPEG	single	-	1-way	-
SNC B2331	box	-	740 x 480	MPEG4 / H.264 / MJPEG	single	-	-	-
SNC B5395	box	-	740 x 480	MPEG4 / MJPEG	single	-	1-way	-
SNC 570	box	-	740 x 480	MPEG4 / MJPEG	single	-	-	-
SNC B2315	box	-	740 x 480	MPEG4 / MJPEG	single	-	1-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
VCC-HD5600PC	PTZ	NET MAIN 1.03-01 (100615-00)	1920 x 1080	H.264 / MJPEG	dual	supported	1-way	-
VCC-HD4000	box	1.00-02 (081027-00)	1920 x 1080	H.264 / MJPEG	single	-	-	-
VCC-HD2500P	box	-	1920 x 1080	H.264 / MJPEG	dual	supported	-	-
VDC-HD3500	Fix dome	NET MAIN 1.03-01 (100618-01) †	1920 x 1080	H.264 / MJPEG	me codec re	supported	-	-
VCC-HD4600	box	NET MAIN 1.03-01 (100614-01) †	1920 x 1080	H.264 / MJPEG	me codec re	supported	1-way	-
VCC-HD5400	PTZ	-	1920 x 1080	H.264 / MJPEG	me codec re	supported	-	-
VDC-HD3100	Fix dome	-	1920 x 1080	H.264 / MJPEG	me codec re	supported	-	-
VDC-HD3300	Fix dome	-	1920 x 1080	H.264 / MJPEG	me codec re	supported	-	-
VCC-HD2100	box	-	1920 x 1080	H.264 / MJPEG	me codec re	supported	-	-
VCC-HD2300	box	-	1920 x 1080	H.264 / MJPEG	me codec re	supported	-	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
RZ-25N	PTZ	-	640 x 480	MPEG4 / JPEG	single	supported	2-way	-
DH180	mini dome	FD8134-VVTK-0100e	Streaming 1	MPEG4 / JPEG	dual	supported	2-way	-



Model	Type	Firmware	Max resolution	Video codec	Stream	Motion detection	Audio	Remark
IP8162P	box	-	1920 x 1080	MPEG4 / H.264 / MJPEG	dual	supported	2-way	-
IP8151P	box	-	1280 x 1024	MPEG4 / H.264 / MJPEG	dual	supported	2-way	-
IP8151	box	IP8151-VVTK-0100e	1280 x 1024	MPEG4 / H.264 / MJPEG	dual	supported	2-way	-
IP7361	bullet	IP7361-VVTK-0101d	1600 x 1200	MPEG4 / H.264	dual	supported	2-way	-
IP7142	bullet	-	720 x 480	MPEG5 / H.264	dual	supported	2-way	-
IP8330	bullet	-	640 x 480	MPEG5 / H.264 / MJPEG	dual	supported	-	-
IP8332	bullet	IP8332-VVTK-0100g	1280 x 800	MPEG4 / H.265	dual	supported	-	-
IP7330	bullet	-	640 x 480	MPEG4 / MJPEG	dual	supported	-	-
IP8161	box	IP8161-VVTK-0100m	1600 x 1200	MPEG4 / H.264 / MJPEG	dual	supported	2-way	-
IP7161	box	IP8161-VVTK-0100m	1600 x 1200	MPEG5 / MJPEG	dual	supported	2-way	-
IP7160	box	-	1600 x 1200	MPEG4 / MJPEG	dual	supported	2-way	-
IP7251	box	-	640 x 480	MPEG5 / MJPEG	dual	supported	2-way	-
IP7154	box	-	640 x 480	MPEG5 / MJPEG	dual	supported	2-way	-
IP7153	box	-	640 x 480	MPEG5 / MJPEG	dual	supported	2-way	-
IP7130	box	-	640 x 480	MPEG4 / MJPEG	dual	supported	2-way	-
IP8132	cube	-	1280 x 800	H.264 / MJPEG	dual	supported	1-way	-
IP7134	cube	-	640 x 480	MPEG4 / MJPEG	dual	supported	2-way	-
IP7133	cube	-	640 x 480	MPEG4 / MJPEG	dual	supported	2-way	-
SD7313 / SD7323	speed dome	SD7151-VVTK-0300a	704 x 576	MPEG5 / MJPEG	dual	supported	2-way	-
SD7151	speed dome	SD7151-VVTK-0300a	640 x 480	MPEG4 / MJPEG	dual	supported	2-way	-
SD8111 / SD8121	speed dome	SD7151-VVTK-0300a	720 x 576	MPEG4 / H.264 / MJPEG	dual	supported	2-way	-
FD8361	fixed dome	-	640 x 480	MPEG4 / H.264 / MJPEG	dual	supported	2-way	-
FD8361L	fixed dome	FD7141-VVTK-0101b	640 x 480	MPEG4 / H.264 / MJPEG	dual	supported	-	-
FD7141	fixed dome	-	640 x 480	MPEG4	dual	supported	2-way	-
FD8161	fixed dome	IP8162-VVTK-0100f	1600 x 1200	MPEG4 / H.264 / MJPEG	dual	supported	2-way	-
FD7132	fixed dome	IP8162-VVTK-0100f	640 x 480	MPEG4 / MJPEG	dual	supported	2-way	-
MD7560	fixed dome	-	1600 x 1200	MPEG4 / MJPEG	dual	supported	2-way	-
MD7530	fixed dome	-	640 x 480	MPEG4 / MJPEG	dual	supported	2-way	-
FD8134	dome	FD8134-VVTK-0100e	1280 x 800	MPEG4 / H.264 / MJPEG	dual	supported	-	-
FD8134V	dome	-	1280 x 800	MPEG4 / H.264 / MJPEG	dual	supported	-	-
FD8133	fixed dome	-	1280 x 800	MPEG4 / H.264 / MJPEG	dual	supported	-	-
FD8133V	fixed dome	-	1280 x 800	MPEG4 / H.264 / MJPEG	dual	supported	-	-
FD8162V	fixed dome	FD8162-VVTK-0100a	1920 x 1080	MPEG4 / H.264 / MJPEG	dual	supported	2-way	-