

All New Enterprise Storage

fast and reliable expansion external storage

Instek Digital™ IP SAN JBOD external storage is available in 12, 16 and 60 hard-drive disc bays and a 12Gb/s SAS based. It offers exceptional storage capacity up to 444 drives.

Simple installation and high availability thanks to features such as dual redundant power supplies render Instek Digital™ DS2400-JB enclosures an attractive choice for flexible scalability.



Key Features

- 12Gb/s SAS connectivity
- S.M.A.R.T. support
- Automatic bad-sector reassignment
- Dedicated bandwidth to each connected drive
- 80 PLUS certified power supply delivering more than 80% energy efficiency
- Intelligent multi-level drive spin-down
- Redundant hot-swappable hardware modules

INSTEK DIGITAL

Instek Digital is a video surveillance business unit of Good Will Instrument Co., Ltd. and focus on the development of high quality digital surveillance solutions. The company inherited over 20-years of surveillance experience. Instek Digital has the luxury of a strong financial background supported by Good Will Instrument Co., Ltd. – has over 40-years of electronics R&D and manufacturing experience. And Good Will Instrument Co., Ltd. is also listed on the Taiwan Stock Exchange.

Instek Digital offers a wide array of video surveillance software and hardware – under the brand of Instek Digital. The core design are based on the following principles; “User-Friendliness”, “Scalability” and “Reliability”. Instek Digital’s solutions are based on an open platform – creating seamless third party integration. With this concept Instek Digital has created a business model that can meet every aspect in today’s surveillance demand. The results speak for themselves – based on small and large projects that we have deployed around the world.


Model	HR-DS2460L-JB
Host (NVR) connectivity	2x12Gb/s SAS ports
	per controller
Hard-disc drive trays	60
Availability and reliability	redundant- hot-swappable modules
Form factor	4U rack-mountable
Power output	AC voltage: 100VAC @ 8A to 240VAC @ 4A with PFC (auto-switching)
PSU (80 PLUS-certified)	2 x 1200W
Operating temperature	0 to 40°C operating/-40 to 60°C non-operating
Humidity	max. 90%, non-condensing
Dimension (WxDxH mm)	640 x 1150 x 470 (with box)
	448 x 840 x 176 (without box)
Weight (kg)	61.2 (with box)
	51.0 (without box)

1) Product specifications and availability are subject to change without notice.
2) Instek Digital is a registered trademark of Good Will Instrument Co., Ltd.
For the latest compatibility details, please contact our sales representatives.


Model	HR-DS2416-JB	HR-DS2412-JB
Host (NVR) connectivity	2x12Gb/s SAS ports	2x12Gb/s SAS ports
	per controller	per controller
Hard-disc drive trays	16	12
Availability and reliability	redundant- hot-swappable modules	
Form factor	3U rack-mountable	2U rack-mountable
Power output	AC voltage: 100VAC @ 8A to 240VAC @ 4A with PFC (auto-switching)	
PSU (80 PLUS-certified)	2 x 530W	2 x 460W
Operating temperature	0 to 40°C operating/-40 to 60°C non-operating	
Humidity	max. 90%, non-condensing	
Dimension (WxDxH mm)	590 x 780 x 430 (with box)	590 x 790 x 380 (with box)
	447 x 500 x 130 (without box)	447 x 500 x 88 (without box)
Weight (kg)	26.1 (with box)	21.9 (with box)
	23.5 (without box)	19.5 (without box)

1) Product specifications and availability are subject to change without notice.
2) Instek Digital is a registered trademark of Good Will Instrument Co., Ltd.
For the latest compatibility details, please contact our sales representatives.


Front View | DS2460L-JB




Rear View | DS2460L-JB




Front View | DS2316-JB



Rear View | DS2316-JB



Front View | DS2212-JB



Rear View | DS2212-JB

